



LCIE

LICENCE



APPAREILLAGE ELECTRIQUE DOMESTIQUE

LCIE N° : NF012_1881

Titulaire :
License Holder:

LEGRAND FRANCE
128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY
87045 LIMOGES CEDEX - FRANCE

Site de fabrication :
Factory:

N° 0212AP,
N° 0010AP,
N° 0002AP,
N° 1456AP

Produit :
Product:

Socle fixe de prise de courant
Fixed socket-outlet

Marque commerciale (s'il y a lieu) :
Trade mark (if any):



Modèle, type, référence :
Model, type, reference:

Gamme / Series : MOSAIC
Références / References : voir annexe / see annex

Caractéristiques principales :
Main characteristics:

16 A, 250 V~

Informations complémentaires :
Additional information:

/

Le produit est conforme à :
The product is in conformity with:

NF C 61-314:2008 +A1:2010

Documents pris en compte :
Relevant documents:

Rapport(s) d'essai(s)/Test report(s) n° 158526-730178B
et rapports listés en annexe / and reports listed in annex

Annule et remplace (s'il y a lieu) :
Cancels and replaces (if necessary):

La licence / License NF012_1406 du/of 09/01/2018 : Ajout de
références produit/addition product references

En vertu de la présente décision notifiée par le LCIE organisme mandaté, AFNOR Certification accorde le droit d'usage de la Marque NF à la société qui en est titulaire pour les produits visés ci-dessus, dans les conditions définies par les règles générales de la Marque NF et par les règles de certification NF, pour autant que les contrôles réguliers de la fabrication et les vérifications par tierce partie soient satisfaisants.


On the strength of the present decision notified by LCIE mandated certification body, AFNOR Certification grants the right to use the NF Mark to the licence holder for the above mentioned products, within the frame of the general rules of the NF Mark and of the NF certification rules, as far as the regular checking and third party verifications of the production are satisfactory.

Fontenay-aux-Roses, 10/04/2019

Date de fin de validité / Expiry date : 01/01/2023

La validité de la présente licence cesse dès l'annulation de l'une des normes sur lesquelles elle est fondée.

The present license is valid until the cancellation of one of the standards on which it is based.



Jean-François BRUEL
Responsable Certification/Certification Officer



Accréditation
N° 5-0014

Portée disponible sur
www.cofrac.fr

LCIE

Laboratoire Central des Industries Electriques
Une société de Bureau Veritas

33 Avenue du Général Leclerc
92260 Fontenay-aux-Roses
FRANCE

WWW.LCIE.FR

Annexe de la licence / Annex of license NF012_1881

Documents pris en compte / Relevant documents :

Rapports d'essai/Test reports : n° 80640-569801/A1, 60021487-514363A/A1, 60032291-530935A/A1, 60051320-552098/A1, 60051320-552296A/A1, 60051549-552343A/A1, 60052084-553026/A1, 109475-618400A, 112252-623334A, 118896-637230A1, 127649-655969, 130899-663536Cr2016-10-05, 136736-675846A, 140943-683663, 140943-683665A, 158526-730178F

RÉFÉRENCES - CARACTÉRISTIQUES PRINCIPALES / REFERENCES - MAIN CHARACTERISTICS

Feuille de norme / <i>standard sheet</i>	I (2P+T) / IIIA (2P)
Courant nominal / <i>rated current (A)</i> Tension nominale / <i>rated voltage (V)</i>	16 A 250 V~
Degré de protection <i>Degree of protection</i>	IP20 IP44 with cover plate 0 788 80 or plates 0 897--
Présence de contact de terre <i>Provision for earthing</i>	sans contact de terre – <i>without earthing contact</i> avec contact de terre – <i>with earthing contact</i>
Procédé de raccordement du câble <i>method of connecting the cable</i>	démontable <i>rewirable</i>
Type des bornes <i>Type of terminals</i>	bornes à vis – <i>screw-type</i> sans vis (rigide et souple) <i>screwless– (rigid and flexible)</i>
Degré de protection contre les chocs électriques <i>Degree of protection against electric shock</i>	protection normale – <i>normal protection</i>
Présence des obturateurs <i>Existence of shutters</i>	avec obturateurs - <i>with shutters</i>
Mode de pose - utilisation <i>Method of application - mounting</i>	En saillie ou encastré <i>Surface type or flush-type</i> Encastré dans le sol avec l'accessoire 0 897-- <i>floor-type with plates 0 897--</i>
Procédé d'installation <i>Method of installation</i>	conception A / <i>design A</i> design B with plates 0 897--

Annexe de la licence / Annex of license NF012_1881

Type reference	References	Number of sockets	Terminals	Colour of cover	Specificity
PFA1	0 771 11	1 x 2P+E	slit	white or black or grey	
	0 995 94	1 x 2P+E	slit	white	
	0 996 95	1 x 2P+E	slit	white	
	0 996 80	1 x 2P+E	slit	white	
	0 771 99	1 x 2P+E	slit	white	
	0 771 12	1 x 2P+E	slit	white antibacterial or grey	with pilot light
	0 787 01	1 x 2P+E	slit	white antibacterial	
	0 771 16	1 x 2P+E	slit	green antibacterial	
	0 771 46	1 x 2P+E	slit	green antibacterial	for Czech Republic
	0 771 17	1 x 2P+E	slit	orange antibacterial	
	0 771 47	1 x 2P+E	slit	orange antibacterial	for Czech Republic
	0 771 18	1 x 2P+E	slit	red antibacterial	
	0 771 26	1 x 2P+E	slit	red antibacterial	with pilot light
	0 771 41	1 x 2P+E	slit	red antibacterial	for Czech Republic
	0 771 19	1 x 2P+E	slit	white	with lid
	0 771 49	1 x 2P+E	slit	white	for Czech Republic with lid
	0 791 21	1 x 2P+E	slit	anthracite	
	0 792 71	1 x 2P+E	slit	aluminium	
	0 792 14	1 x 2P+E	slit	aluminium	for Czech Republic
	0 771 32	1 x 2P+E	slit	white antibacterial	mobile face of entry plug
	0 996 24	1 x 2P+E	slit	white antibacterial	mobile face of entry plug
	0 791 32	1 x 2P+E	slit	anthracite	mobile face of entry plug
	0 771 33	1 x 2P+E	slit	red antibacterial	mobile face of entry plug
	0 771 35	1 x 2P+E	slit	white antibacterial	with pilot light mobile face of entry plug
	0 787 04	1 x 2P+E	slit	green antibacterial	mobile face of entry plug
	0 921 10	1 x 2P+E	slit	Inox	
	0 921 11	1 x 2P+E	slit	Inox	

slit : sans vis / screwless (rigid and flexible)

Annexe de la licence / Annex of license NF012_1881

Type reference	References	Number of sockets	Terminals	Colour of cover	Specificity
PFA2	0 771 10	1 x 2P	slt	white	
	0 996 41	1 x 2P	slt	white	
	0 996 94	1 x 2P	slt	white	
PFA3	0 771 45	1 x 2P+E	slt	white	angle of 45°
	0 793 45	1 x 2P+E	slt	black	angle of 45°
	0 771 48	1 x 2P+E	slt	white	with pilot light angle of 45°
PFAD1	0 771 34	2 x 2P+E	slt	white	mobile face of entry plug
	0 791 34	2 x 2P+E	slt	anthracite	mobile face of entry plug
	0 793 44	2 x 2P+E	slt	aluminium	mobile face of entry plug
PFAT1	0 771 36	3 x 2P+E	slt	white	mobile face of entry plug
	0 791 36	3 x 2P+E	slt	anthracite	mobile face of entry plug
	0 793 46	3 x 2P+E	slt	aluminium	mobile face of entry plug
	0 771 13	1 x 2P+E	st	white	
	0 996 40	1 x 2P+E	st	white	
	0 771 14	1 x 2P+E	st	red or grey / red	tamperproof
	0 771 15	1 x 2P+E	st	red antibacterial	tamperproof with pilot light

st : À vis / *screw-type*
slt : sans vis / *screwless* (rigid and flexible)

Annexe de la licence / Annex of license NF012_1881

Type reference	References	Number of sockets	Terminals	Colour of cover	Specificity
E11	0 771 42	2 x 2P+E	slt	white	for trunking angle of 45°
	0 793 62	2 x 2P+E	slt	black	for trunking angle of 45°
	0 996 42	2 x 2P+E	slt	white	for trunking angle of 45°
	200 020	2 x 2P+E	slt	white	for trunking angle of 45°
	200 021	2 x 2P+E	slt	white	for trunking angle of 45°
	0 771 62	2 x 2P+E	slt	green	for trunking angle of 45°
	0 791 92	2 x 2P+E	slt	anthracite	for trunking angle of 45°
	0 792 72	2 x 2P+E	slt	aluminium	for trunking angle of 45°
	0 771 72	2 x 2P+E	slt	red	for trunking angle of 45°
	0 771 64	2 x 2P+E	slt	white	for trunking angle of 45° grey push terminal
	0 792 76	2 x 2P+E	slt	aluminium	for trunking angle of 45° grey push terminal
	0 771 68	2 x 2P+E	slt	red	for trunking angle of 45° grey push terminal
	0 771 43	3 x 2P+E	slt	white	for trunking angle of 45°
	0 793 63	3 x 2P+E	slt	black	for trunking angle of 45°
	0 996 43	3 x 2P+E	slt	white	for trunking angle of 45°
	0 771 63	3 x 2P+E	slt	green	for trunking angle of 45°
	0 791 63	3 x 2P+E	slt	anthracite	for trunking angle of 45°
	0 792 73	3 x 2P+E	slt	aluminium	for trunking angle of 45°
	0 771 73	3 x 2P+E	slt	red	for trunking angle of 45°
	0 771 65	3 x 2P+E	slt	white	for trunking angle of 45° grey push terminal
	0 771 69	3 x 2P+E	slt	red	for trunking angle of 45° grey push terminal
	0 771 44	4 x 2P+E	slt	white	for trunking angle of 45°
	0 996 31	4 x 2P+E	slt	white	for trunking angle of 45°
	200 022	4 x 2P+E	slt	white	for trunking angle of 45°
	200 023	4 x 2P+E	slt	white	for trunking angle of 45°
	0 771 74	4 x 2P+E	slt	red	tamperproof for trunking angle of 45°
	0 771 52	2 x 2P+E	slt	red	tamperproof for trunking angle of 45°
	0 771 66	2 x 2P+E	slt	red	tamperproof for trunking angle of 45° grey push terminal
	0 771 53	3 x 2P+E	slt	red	tamperproof for trunking angle of 45°
	0 771 67	3 x 2P+E	slt	red	tamperproof for trunking angle of 45° grey push terminal
0 771 54	4 x 2P+E	slt	red	tamperproof for trunking angle of 45°	

slt : sans vis / screwless (rigid and flexible)

Annexe de la licence / Annex of license NF012_1881

Type reference	References	Number of sockets	Terminals	Colour of cover	Specificity
E10	0 771 01	1 x 2P+E	slt	white	for trunking with soluclip
	0 771 02	2 x 2P+E	slt	white	for trunking with soluclip
	0 771 82	2 x 2P+E	slt	black	for trunking with soluclip
	0 771 92	2 x 2P+E	slt	green	for trunking with soluclip
	0 771 03	3 x 2P+E	slt	white	for trunking with soluclip
	0 771 83	3 x 2P+E	slt	black	for trunking with soluclip
	0 771 04	4 x 2P+E	slt	white	for trunking with soluclip
	0 771 21	1 x 2P+E	slt	red	tamperproof for trunking with soluclip
	0 771 22	2 x 2P+E	slt	red	tamperproof for trunking with soluclip
	0 771 23	3 x 2P+E	slt	red	tamperproof for trunking with soluclip
	0 771 24	4 x 2P+E	slt	red	tamperproof for trunking with soluclip
	0 773 31	1 x 2P+E	slt	white	for trunking
	0 773 32	2 x 2P+E	slt	white	for trunking
	0 773 33	3 x 2P+E	slt	white	for trunking
	0 773 34	4 x 2P+E	slt	white	for trunking
	0 773 41	1 x 2P+E	slt	red	tamperproof for trunking
	0 773 42	2 x 2P+E	slt	red	tamperproof for trunking
	0 773 43	3 x 2P+E	slt	red	tamperproof for trunking
	0 773 44	4 x 2P+E	slt	red	tamperproof for trunking
	0 773 01	1 x 2P+E	slt	white	for trunking
	0 773 51	1 x 2P+E	slt	white	for trunking with frame cv 65
	0 773 02	2 x 2P+E	slt	white	for trunking
	0 773 52	2 x 2P+E	slt	white	for trunking with frame cv 65
	0 792 22	2 x 2P+E	slt	aluminium	tamperproof for trunking
	0 773 03	3 x 2P+E	slt	white	tamperproof for trunking
	0 792 23	3 x 2P+E	slt	aluminium	tamperproof for trunking
	0 773 04	4 x 2P+E	slt	white	tamperproof for trunking
	0 773 54	4 x 2P+E	slt	white	tamperproof for trunking with frame cv 65
	0 773 21	1 x 2P+E	slt	red	Tamperproof for trunking
	0 773 22	2 x 2P+E	slt	red	Tamperproof for trunking
	0 773 23	3 x 2P+E	slt	red	Tamperproof for trunking
	0 773 24	4 x 2P+E	slt	red	Tamperproof for trunking
LXX08	0 771 61	2P+E	slt	white	with USB type C
	0 793 61	2P+E	slt	aluminium	with USB type C

slt : sans vis / screwless (rigid and flexible)

Component	Model	Manufacturer	Conformity
USB type C	LXX08	LEGRAND	TR LCIE 158526-730181

Annexe de la licence / Annex of license NF012_1881

Accessoires / Accessories :

Blank

References	Number of modules	Colour
0 770 70	1	white
0 792 70	1	aluminium
0 787 20	1	white antibacterial
0 770 71	2	white
0 791 81	2	anthracite
0 792 80	2	aluminium
0 787 21	2	white antibacterial
4 129 52	2	grey

Pilot light

References	Voltage	Specificity
0 676 63	230V	Indicator green
0 676 64	230V	Indicator white

Frames

Between axes: 71mm, with screw

References	Number of gang or modules	Specificity
0 802 51	1 gang	
0 802 09	1 gang	sold by 100
0 802 60	1 gang	for illumination under frame
0 802 62	1 gang	for indicator under frame
0 802 59	3 modules	
0 802 52	2 gangs	
0 802 58	2 gangs	horizontal for illumination under frame
0 802 57	2 gangs	vertical for illumination under frame
0 802 53	3 gangs	
0 802 54	4 gangs	
0 802 64	2 x 2 gangs	
0 802 66	2 x 3 gangs	
0 802 68	2 x 10 modules	

Between axes: 71mm, with claws

References	Number of gang	Specificity
0 802 61	1 gang	
0 802 69	1 gang	long claws

Between axes: Italy

References	Number of modules	Specificity
0 802 13	3 modules	
0 802 14	4 modules	
0 802 16	6 modules	
0 802 93	3 modules CHILI	

Annexe de la licence / Annex of license NF012_1881

Frame DLP

References	Number of modules	Specificity
0 109 21	2 modules	cv 65
0 109 41	4 modules	
0 109 61	6 modules	
0 109 81	8 modules	
0 109 22	2 modules	cv 85
0 109 42	4 modules	
0 109 62	6 modules	
0 109 82	8 modules	

Blanks

References	Number of gang
0 791 04	2 gangs
0 791 06	3 gangs
0 791 10	4 gangs

Thin walls

References	Number of modules	Colour
0 802 91	2 modules	white
0 802 95	2 modules	aluminium

Modulars

References	Number of modules	Colour	Specificity
0 788 40	2 modules	white	cover for modular
0 801 29	2 modules	white	DIN rail for modular
0 802 99	2 modules	white	modular support
4 129 50	2 modules	white	modular support

Kit box + frame + plate

References	Number of modules	Colour
0 788 72	2 x 4 modules	white
0 788 73	3 x 4 modules	white
0 788 74	4 x 4 modules	white
0 790 72	2 x 4 modules	aluminium
0 790 73	3 x 4 modules	aluminium
0 790 74	4 x 4 modules	aluminium

Kit surface box + frame + plate

Export references	France references	Number of modules	Colour
0 788 82	0 788 86	2 x 4 modules	white
0 788 83	0 788 87	3 x 4 modules	white
0 788 84	0 788 88	4 x 4 modules	white
0 790 82		2 x 4 modules	aluminium
0 790 83		3 x 4 modules	aluminium
0 790 84		4 x 4 modules	aluminium

Annexe de la licence / Annex of license NF012_1881

Boxes for surface mounting

References	Number of gang or modules	Specificity
0 802 80	1 gang	Depth 30mm
0 802 81	1 gang	Depth 40mm
0 802 82	2 gangs	vertical
0 802 83	3 gangs	vertical
0 802 84	4 gangs	
0 802 85	2 gangs	horizontal
0 802 86	3 gangs	horizontal
0 802 89	3 modules	
0 802 74	2 x 2 gangs	
0 802 76	2 x 3 gangs	
0 802 78	2 x 10 modules	

Plates for floor recessed type

References	Designation
0 897 00	Square plate to be equipped, 1 gang inox - IP44, IK08
0 897 01	Round plate to be equipped, 1 gang inox - IP44, IK08
0 897 10	Square plate to be equipped, 1 gang bronze - IP44, IK08
0 897 11	Round plate to be equipped, 1 gang bronze - IP44, IK08
0 897 02	Rectangle plate to be equipped, 2 gang inox - IP44, IK08
0 897 12	Rectangle plate to be equipped, 2 gang bronze - IP44, IK08

Cover plates

Between axes: 71mm

References	Number of gang or modules	Colour	Specificity	Frame
0 788 02	1 gang 2 modules	white	sold by 100	0 802 51, 0 802 60, 0 802 61, 0 802 62, 0 802 69
0 788 99		white		
0 790 02		aluminium Z		
0 787 22		white antibacterial		
0 793 02		aluminium		
0 790 42		anthracite		
0 788 03	3 modules	white		0 802 59
0 790 03		aluminium Z		
0 793 03		aluminium		
0 788 04	2 x 2 modules	white	horizontal	0 802 52, 0 802 58
0 787 25		white antibacterial		
0 793 04		aluminium		
0 790 44		anthracite		
0 788 22	2 x 2 modules	white	vertical	0 802 52, 0 802 57
0 787 23		white antibacterial		
0 793 22		aluminium		
0 790 62		anthracite		
0 788 14	4 modules	white	horizontal	0 802 52, 0 802 58
0 790 14		aluminium Z		
0 787 24		white antibacterial		
0 793 14		aluminium		
0 790 54		anthracite		
0 788 25	5 modules	white	vertical	0 802 52, 0 802 57
0 790 25		aluminium Z		
0 793 25		aluminium		
0 788 15	5 modules	white	horizontal	0 802 52, 0 802 58
0 793 15		aluminium		

Annexe de la licence / Annex of license NF012_1881

Cover plates Between axes: 71mm

References	Number of gang or modules	Colour	Specificity	Frame
0 788 06	3 x 2 modules	white	horizontal	0 802 53
0 793 06		aluminium		
0 790 46		anthracite		
0 788 23	3 x 2 modules	white	vertical	0 802 53
0 790 23		aluminium Z		
0 793 23		aluminium		
0 788 16	6 modules	white		0 802 53
0 790 16		aluminium Z		
0 787 26		white antibacterial		
0 793 16		aluminium		
0 790 56		anthracite		
0 788 18	8 modules	white		0 802 53
0 790 18		aluminium Z		
0 793 18		aluminium		
0 790 58		anthracite		
0 788 38	2 x 2 x 2 modules	white		0 802 64
0 790 38		aluminium Z		
0 793 38		aluminium		
0 788 30	2 x 5 modules	white		0 802 64
0 793 30		aluminium		
0 788 32	2 x 3 x 2 modules	white		0 802 66
0 790 32		aluminium Z		
0 793 32		aluminium		
0 788 36	2 x 6 modules	white		0 802 66
0 790 36		aluminium Z		
0 793 36		aluminium		
0 790 76		anthracite		
0 788 37	2 x 8 modules	white		0 802 66
0 793 37		aluminium		
0 790 77		anthracite		
0 788 08	4 x 2 modules	white	horizontal	0 802 54
0 790 08		aluminium Z		
0 793 08		aluminium		
0 788 10	10 modules	white		0 802 54
0 790 10		aluminium Z		
0 793 10		aluminium		
0 788 28	2 x 10 modules	white		0 802 68
0 793 28		aluminium		

Annexe de la licence / Annex of license NF012_1881

Cover plates

Between axes: 57mm

References	Number of modules	Colour	Specificity	Frame
0 788 54	2 x 2 modules	white	vertical	0 802 51, 0 802 61
0 793 54		aluminium		
0 788 64	2 x 2 modules	white	horizontal	0 802 51, 0 802 61, 0 802 14
0 793 64		aluminium		
0 788 56	3 x 2 modules	white	vertical	0 802 51, 0 802 61
0 788 66	3 x 2 modules	white	horizontal	0 802 51, 0 802 61, 0 802 16

Between axes: Italy

References	Number of modules	Colour	Specificity	Frame
0 788 91	1 module	white		0 802 13, 0 802 93
0 788 92	2 modules	white	centred	0 802 13, 0 802 94
0 788 93	3 modules	white	vertical	0 802 13, 0 802 95
0 788 94	2 modules	white	separated	0 802 13, 0 802 96
0 788 90		white	blank	0 802 13, 0 802 97

Cover IP 44

References	Number of modules	Colour	Specificity	Frame
0 788 80	2 modules	white antibacterial	IP44	0 802 51, 0 802 61