



LAMPES BA9s et E10 10x28mm

Ø 10 x 28 mm – E 10 et BA 9 s

u.v	Réf.		U V	I mA	P W	Durée vie AC Life h	Filament	Code gestion	
	E 10	BA 9 s						E 10	BA 9 s
10/100	AB 1460		4.5	100	0.5	1000	C 2 R	120 110	
10/100	AB 1470		4.5	300	1.5	1000	C 2 R	120 116	
10/100	AB 1472	AB 1469	5	90	0.5	2000	C 2 R	120 122	121 122
10/100	AB 1473	AB 1474	6	50	0.3	2000	C 2 R	120 128	121 128
10/100	AB 1475	AB 1476	6	100	0.6	2000	C 2 R	120 134	121 134
10/100		AB 1477	6	180	1.1	2000	C 2 R		121 140
10/100	AB 1478	AB 1479	6	200	1.2	2000	C 2 R	120 146	121 146
10/100	AB 1480	AB 1490	6	330	2.0	2000	C 2 R	120 152	121 152
10/100	AB 1500	AB 1510	6	500	3.0	1000	C 2 R	120 158	121 158
10/100	AB 1513	AB 1514	6	670	4.0	1000	C 2 R	120 164	121 164
10/100	AB 1520	AB 1530	6.5	100	0.7	1000	C 2 R	120 170	121 170
10/100	AB 1540	AB 1550	6.5	150	1.0	2000	C 2 V	120 176	121 176
10/100	AB 1560	AB 1570	6.5	300	2.0	1000	C 2 V	120 182	121 182
10/100	AB 1620	AB 1630	7	100	0.7	2000	C 2 V	120 188	121 188
10/100	AB 1640	AB 1650	7	300	2.0	1000	C 2 V	120 194	121 194
10/100	AB 1660		12	20	0.2	1000	C 2 V	120 200	
10/100	AB 1680	AB 1690	12	50	0.6	1000	C 2 V	120 206	121 206
10/100	AB 1700	AB 1710	12	100	1.2	2000	C 2 V	120 212	121 212
10/100	AB 1715	AB 1716	12	120	1.4	2000	C 2 V	120 218	121 218
10/100	AB 1720	AB 1730	12	170	2.0	2000	C 2 V	120 224	121 224
10/100	AB 1750	AB 1760	12	250	3.0	2000	C 2 V	120 230	121 230
10/100		AB 1780	12	330	4.0	1000	C 2 V		121 236
10/100	AB 1782	AB 1783	14	80	1.1	1000	C 2 V	120 242	121 242
10/100	AB 1790		16	190	3.0	1000	C 2 V	120 248	
10/100	AB 1800	AB 1810	18	100	1.8	1000	C 2 V	120 254	121 254
10/100	AB 1813		18	166	3.0	1000	C 2 V	120 260	
10/100	AB 1820	AB 1825	24	50	1.2	1000	C 2 F	120 266	121 266
10/100	AB 1830	AB 1840	24	85	2.0	2000	C 2 F	120 272	121 272
10/100	AB 1860	AB 1870	24	125	3.0	1000	C 2 F	120 278	121 278
10/100	AB 1880	AB 1890	24	170	4.0	1000	C 2 F	120 284	121 284
10/100	AB 1893	AB 1894	26	75	2.0	1000	C 2 F	120 290	121 290
10/100	AB 1896	AB 1897	27	75	2.0	1000	C 2 F	120 296	121 296
10/100	AB 1900	AB 1910	28	40	1.0	1000	C 2 F	120 302	121 302
10/100		AB 1920	28	100	2.8	1000	C 2 F		121 308
10/100		AB 1930	28	170	4.8	1000	C 2 F		121 314
10/100	AB 1940	AB 1950	30	50	1.5	1000	C 2 F	120 320	121 320
10/100		AB 1955	30	66	2.0	1000	C 2 F		121 326
10/100	AB 1960	AB 1970	30	100	3.0	1000	C 2 F	120 332	121 332
10/100	AB 2040	AB 2050	36	50	1.8	1000	C 2 F	120 338	121 338
10/100	AB 2060	AB 2070	36	80	3.0	2000	C 2 F	120 344	121 344
10/100	AB 2100	AB 2110	48	40	2.0	2000	C 2 F	120 350	121 350
10/100	AB 2140	AB 2150	48	50	2.4	1000	C 2 F	120 356	121 356
10/100	AB 2160	AB 2170	48	60	3.0	2000	C 2 F	120 362	121 362
10/100	AB 2190	AB 2200	48	80	4.0	1000	C 2 F	120 368	121 368
10/100	AB 2214	AB 2215	52	60	3.0	1000	C 2 F	120 374	121 374
10/100	AB 2220	AB 2230	60	20	1.2	2000	CC 2 F	120 380	121 380
10/100	AB 2240	AB 2250	60	35	2.0	1000	CC 2 F	120 386	121 386
10/100	AB 2251	AB 2252	60	40	2.4	1000	CC 2 F	120 392	121 392
10/100	AB 2260	AB 2270	60	50	3.0	2000	CC 2 F	120 398	121 398
10/100	AB 2290	AB 2300	60	70	4.0	1000	CC 2 F	120 404	121 404
10/100	AB 2310		70	40	3.0	1000	CC 2 F	120 410	
10/100		AB 2324	85	25	2.0	1000	CC 2 F		121 416
10/100	AB 2325	AB 2326	85	35	3.0	1000	CC 2 F	120 422	121 422
10/100	AB 2330	AB 2340	130	15	2.0	1500	C 5 A	120 428	121 428
10/100	AB 2344	AB 2345	130	20	2.6	1500	C 5 A	120 434	121 434
10/100	AB 2350	AB 2360	160	20	3.0	1500	C 5 A	120 440	121 440
10/100	AB 2365	AB 2366	230	9	2.0	1000	CC 7 A	120 446	121 446
10/100	AB 2370	AB 2380	240	13	3.0	1000	C 7 A	120 452	121 452
10/100	AB 2383	AB 2384	240	17	4.0	1000	C 7 A	120 458	121 458
10/100	AB 2385	AB 2386	230	22	5.0	700	CC 7 A	120 464	121 464



Garantie

Pour plus de détails sur les garanties et les conditions d'extension de garantie, voir aussi:

www.auroralighting.com

Adresse en France

AURORA
ZAC Entrée Sud de Gonesse,
1, rue Jean Mermoz
95500 Gonesse, France
PH: +33 (0) 1 30 11 11 88
FX: +33 (0) 1 39 86 07 28